

EX-PROOF PRIRIO PANEL

The Ex-Proof Pririo Panel is heat and impact resistant which makes it great for industrial warehouses and plant workshops. The body of the luminaire is aluminium injection frame with electrostatic coating with highly transmissive clear tempered glass coating.



| | | | | | | |
|---------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Wattage | 50 | 75 | 100 | 125 | 150 | 200 |
| Lm/W | 160 | 160 | 160 | 160 | 160 | 160 |
| Dimensions | 342 x 342 x 160mm | 342 x 342 x 160mm | 342 x 342 x 160mm | 342 x 342 x 160mm | 342 x 342 x 160mm | 342 x 342 x 160mm |
| Weight | 8kg | 8kg | 8kg | 8kg | 8kg | 8kg |
| Power Factor | >0.95 | >0.95 | >0.95 | >0.95 | >0.95 | >0.95 |
| Input Voltage | AC220-240V | AC220-240V | AC220-240V | AC220-240V | AC220-240V | AC220-240V |
| Input Frequency | 50/60Hz | 50/60Hz | 50/60Hz | 50/60Hz | 50/60Hz | 50/60Hz |
| Colour Temperature | 3000K, 4000K & 6500K | 3000K, 4000K & 6500K | 3000K, 4000K & 6500K | 3000K, 4000K & 6500K | 3000K, 4000K & 6500K | 3000K, 4000K & 6500K |
| LED Lifespan | 63,000hrs | 63,000hrs | 63,000hrs | 63,000hrs | 63,000hrs | 63,000hrs |
| Colour | Yellow | Yellow | Yellow | Yellow | Yellow | Yellow |
| Luminaire Material | Aluminium | Aluminium | Aluminium | Aluminium | Aluminium | Aluminium |
| IP Rating | 66 | 66 | 66 | 66 | 66 | 66 |
| Warranty | 10 years | 10 years | 10 years | 10 years | 10 years | 10 years |
| Energy Rating | B | B | B | B | B | B |

